

Heavy Duty Jaw Crusher

With a 1270mm (50") x 735mm (29") single toggle jaw (the widest jaw in its class), the J50 places McCloskey $^{\text{TM}}$ at the fore of portable crushing machinery. Maximum productivity is delivered through the enhancements to the jaw box including heavier flywheels and ptimization for all crushing applications.

The J50's jaw speed leads to better reduction and material being processed faster through the crushing chamber.

McCloskey International has a proven reputation for designing quality, best-in-class equipment and the J50 Crusher brings even more power and productivity together in one machine.

With its class-leading throughput and capacity and the largest stockpile height in its category the J50 crusher continues to push the boundaries of industry performance.

Features

- 1270mm (50") x 735 (29") single toggle jaw
- Track or Track c\w Wheel bogie
- Integrated hydraulic folding hopper
- Integrated hydraulic folding stockpiling conveyors
- I-beam plate fabricated chassis construction
- Large gap between crusher discharge and main conveyor feedboot
- Open chassis design for ease of maintenance
- Fast setup time

McCloskey

Feeder

Folding hopper mounted over vibrating feeder with integral pre-screen. Feeder rate can be by load sensing iaw.

regulated manually or automatically

Crusher Pre-screen

Optional independent crusher pre-screen maximizes crusher efficiency and delivers screened product via side conveyor.

Control Panel

User friendly waterproof and dustproof control panel. Allows monitoring of pressures, fluid levels and fuel consumption. Provides push button control of jaw, track and feeder functions.

48" Extended Conveyor

Extended 48" main conveyor as standard, giving large stockpile capacity. Conveyor lowers and raises hydraulically.

Ideal Transport Size

At only 3.0m wide, the J50 is easily transported between job sites.

Jaw Crusher

True 50" x 29" jaw with reversible hydrostatic drive, reversible jaw plates, and twin hydraulic ram wedge closed side setting (CSS) adjust.

mccloskeyinternational.com

SPECIFICATION DATA

Dimensions and Capacities

Engine 350 Hp (261 kW)

Diesel

Transport Height 11' 4.7" (3.47m)

Transport Length 48' 10.9" (14.91m)

Transport Width 9' 10" (3.0m)

Weight - w/ magnet 112,440 lb & side conveyor (51,000kg)

Crushing Chamber 50" (wide) x 29"

(pitman opening)

Stockpile Height Main Conveyor

13' 11" (4.26m)

Stockpile Height

8' 6" (2.<u>58m</u>)

Side Conveyor

Optional Prescreen

47.4" x 83.4"

Feeder (1.20m x 2.12m)

©Copyright 2020 McCloskey International. All rights reserved. McCloskey is a trademark of McCloskey International.

McCloskey International reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate - McCloskey International assumes no liability resulting from errors or omissions in this document.