



Also available with 4WD.

DEUTZ-FAHR AGROMAXX 55-60



The technical data and pictures are guideline only. Whilst making every effort to meet your requirements, DEUTZ-FAHR may make changes at any time and is not required to give notice thereof.

Produced by Marketing Department - Code 308.8102.3.4-2 - 09/14 - I.P.

TECHNICAL DATA		AGROMAXX	
		55	60
ENGINE			
Emissions		Tier1	Tier1
Manufacturer		SDF 1000.3	SDF 1000.3
Cylinders/Capacity	No./cm3	3/3,000	3/3,000
Natural aspiration		•	•
Max. homologated power (ECE R-120)	kW/hp	37/50	40.5/55
Max. engine speed (rated)	rpm	2,350	2,350
Max. torque	Nm	175	195
Mechanical engine control		•	•
Cyclone prefilter		•	•
Cooling liquid		•	•
Under-hood silencer with vertical exhaust		•	•
Fuel tank capacity	litres	56	56
MECHANICAL GEARBOX			
Synchronised		•	•
Number of speeds	n°	8+2	8+2
Number of speeds with reduction gear	n°	12+3	12+3
Minimum/maximum speed with reduction gear	km/h	0.81/2,91	0,83/2,95
Max. speed	km/h	30	30
Mechanical dry clutch, single		•	•
REAR PTO			
Mechanical dry clutch, single		•	•
Mechanical engagement		•	•
PTO 540		•	•
FRONT AND REAR AXLE			
Front wheel drive mechanically engaged (only 4WD versions)		•	•
Mechanically operated differential lock		•	•
Steering angle/turning circle 2WD	degrees/mm	50°/ 3,550	50°/3,550
Steering angle/turning circle 4WD	degrees/mm	55°/ 3,700	55°/3,700
BRAKES			
Braking system with wet brake discs		•	•
Mechanical parking brake		•	•
STEERING			
Hydrostatic steering with independent pump		•	•
HITCH			
Category		II	II
Mechanical rear hitch		•	•
Rear hitch lift capacity	kg	1,500	1,500
HYDRAULIC SYSTEM			
Pump output (std)	l/min	31	31
Open-centre hydraulic system		•	•
Mechanical valve engagement		•	•
Rear hydraulic auxiliary valves	No. of ways	2/4	2/4
DRIVING POSITION			
Side control levers		•	•
ROPS with two uprights		○	○
Driver seat with mechanical suspension		•	•
Analogue instrumentation		•	•
DIMENSIONS AND WEIGHTS			
Standard rear tyres		14.9R28"	16.9R28"
Max. length	mm	3,202	3,225
Width (min-max)	mm	1,685/2,125	1,822/2,336
Wheelbase (4WD/2WD)	mm	1,975/2,045	1,975/2,045
Front track (4WD/2WD)	mm	1,455/1,250	1,480/1,335
Rear track	mm	1,340	1,410
Max. weight at steering	mm	1,505	1,505
Max. height at cowl	mm	1,355	1,355
Weight with ROPS (4WD/2WD)	kg	2,150/1,940	2,300/2,090

STD • OPT ○

Dealer



Use of original lubricants and coolants is recommended.

DEUTZ-FAHR is a brand of SDF
deutz-fahr.com

